

Item	Product Name	Model	Voltage (V)	Amps	Watts	Max chlorine output	Max copper output	Flow rate requirement	Salt level (g/liter)	Max pool volume
54601	Saltwater System with Copper Ionization	CS8110	110-120 (12v output)	/	125	12g/h	0.36g/h	700-4,000g/h (2,650-15,140 l/h)	2.5 to 3.5 (3 ideal)	Up to 14,364 gal (54,368 L)
54602		CS8220	220-230 (12v output)		125					
54602BS		CS8230	230-240 (12v output)		125					
54602GS		CS8220G	220-230 (12v output)		125					
54611	Saltwater System & Filter Pump with Copper Ionization	CS8111	110-120 (12v output)	/	400	12g/h	0.36g/h	Built-in 2,000g/h (7,050 l/h) pump	2.5 to 3.5 (3 ideal)	Up to 14,364 gal (54,368 L)
54612		CS8221	220-230 (12v output)		400					
54612BS		CS8231	230-240 (12v output)		400					
56677	Sand Filter Pump14" & Saltwater System	CS15110	110-120 (12v output)	/	470	10g/h	0.36g/h	Built-in 1,600 g/h (6,050 l/h) pump	2.5 to 3.5 (3 ideal)	Up to 14,364 gal (54,368 L)
56678		CS15220	220-230 (12v output)							
56678BS		CS15230	230-240 (12v output)							
56681	Sand Filter Pump16" & Saltwater System	CS20110	110-120 (12v output)	/	770	12g/h	0.36g/h	Built-in 2,650 g/h (10,030 l/h) pump	2.5 to 3.5 (3 ideal)	Up to 14,364 gal (54,368 L)
56682		CS20220	220-230 (12v output)							
56682BS		CS20230	230-240 (12v output)							